Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: : Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : HARVEST KING CARB & CHOKE CLEANER 14 OZ.

Product code : HK006

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Cleaner

1.3. Details of the supplier of the safety data sheet

Mid-States Distributing P.O. Box 64537 St. Paul, MN 55164-0537 T 651-698-8831

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Aerosol 2 H223 Press. Gas (Comp.) H280 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Skin Irrit. 2 H315 Eve Irrit. 2A H319 Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



GHS04



GHS06





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation
H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US)

: P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume.gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

28/02/2019 EN (English US) 1/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P307+P311 - If exposed: Call a poison center/doctor P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methanol	(CAS-No.) 67-56-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Toluene	(CAS-No.) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Heptane, Branched Cyclic	(CAS-No.) 426260-76-6	12.24 - 12.75	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 - 10	Press. Gas (Comp.), H280
n-Heptane	(CAS-No.) 142-82-5	3.1875 - 5.7375	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The exact percentage is a trade secret.

First-aid measures after eve contact

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : N

: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call

 Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating.

28/02/2019 EN (English US) 2/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a

poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

Causes serious eye irritation.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust, fume, gas, mist, vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released product, pump into

suitable containers.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray.

28/02/2019 EN (English US) 3/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures

Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact. Observe very strict hygiene - avoid contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

o. 1. Control parameters			
Benzene (71-43-2)			
USA ACGIH	ACGIH TWA (ppm)	1 ppm	
USA ACGIH	ACGIH STEL (ppm)	5 ppm	
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm	
Toluene (108-88-3)			
USA ACGIH	ACGIH TWA (mg/m³)	75 mg/m³	
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm	
n-Heptane (142-82-5)			
USA ACGIH	ACGIH TWA (ppm)	400 ppm	
USA ACGIH	ACGIH STEL (ppm)	500 ppm	
Heptane, Branched Cyclic (426260-76-6)			
USA ACGIH	ACGIH TWA (ppm)	400 ppm	
USA ACGIH	ACGIH STEL (ppm)	500 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm	
Carbon Dioxide, Liquefied,	Under Pressure (124-38-9)		
USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m³	
USA ACGIH	ACGIH TWA (ppm)	5000 ppm	
USA ACGIH	ACGIH STEL (mg/m³)	54000	
USA ACGIH	ACGIH STEL (ppm)	30000 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm	
Methanol (67-56-1)			
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³	
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³	
USA ACGIH	ACGIH STEL (ppm)	250 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	

28/02/2019 EN (English US) 4/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1188 mg/m³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m³)	1782 mg/m³
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to light yellow.

Odor : Solvent-like odour.

Odor threshold : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : < -78 °C (Lowest Component-Acetone)

Boiling point : 56.1 °C (Lowest Component-Acetone)

Flash point : -18 °C (Lowest Component-Acetone)

Auto-ignition temperature : 385 °C (Lowest Component-Acetone)

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 0.82

Solubility : Poorly soluble in water.

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Heating may cause a fire or explosion.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 45 %

Gas group : Compressed gas

28/02/2019 EN (English US) 5/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

todio tomony	. Net sladelined
Benzene (71-43-2)	
LD50 oral rat	> 2000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value Oral)
LC50 inhalation rat (mg/l)	43.767 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
LC50 inhalation rat (ppm)	13700 ppm (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE CLP (vapors)	43.767 mg/l/4h
ATE CLP (dust, mist)	43.767 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
ATE CLP (oral)	5580 mg/kg body weight
n-Heptane (142-82-5)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Read-across, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male/female, Read-across, Dermal)
LC50 inhalation rat (mg/l)	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours))
Heptane, Branched Cyclic (426260-7	76-6)
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Read-across, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male/female, Read-across, Dermal)
LC50 inhalation rat (mg/l)	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours))
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
ATE CLP (oral)	100 mg/kg body weight
ATE CLP (dermal)	300 mg/kg body weight
ATE CLP (gases)	700 ppmV/4h
ATE CLP (vapors)	3 mg/l/4h
ATE CLP (dust, mist)	0.5 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)

28/02/2019 EN (English US) 6/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	-
Acetone (67-64-1)	
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/effects after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.
Symptoms/effects after ingestion	 Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Benzene (71-43-2)			
LC50 fish 1	5.3 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)		
EC50 Daphnia 1	10 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)		
ErC50 (algae)	100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)		
Toluene (108-88-3)			
LC50 fish 1	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value)		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
LC50 fish 1	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)		
Methanol (67-56-1)			
LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)		
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semistatic system, Fresh water, Experimental value, Locomotor effect)		
ErC50 (algae)	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)		
Acetone (67-64-1)			
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)		
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)		
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)		
TLM fish 2	> 1000 ppm (96 h; Pisces)		
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)		
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)		
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)		
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)		

12.2. Persistence and degradability

HARVEST KING CARB & CHOKE CLEANER 14 OZ.		
Persistence and degradability	Not established.	

28/02/2019 EN (English US) 7/14

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD) Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD) n-Heptane (142-82-5)	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. 2.18 g O ₂ /g substance 2.15 g O ₂ /g substance 3.1 g O ₂ /g substance 0.7 Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD) Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. 2.18 g O ₂ /g substance 2.15 g O ₂ /g substance 3.1 g O ₂ /g substance 0.7 Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 3.69
Chemical oxygen demand (COD) ThOD BOD (% of ThOD) Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	2.15 g O ₂ /g substance 3.1 g O ₂ /g substance 0.7 Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
ThOD BOD (% of ThOD) Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	3.1 g O ₂ /g substance 0.7 Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
BOD (% of ThOD) Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Toluene (108-88-3) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	Biodegradable in the soil. Readily biodegradable in water. 2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	2.15 g O ₂ /g substance 2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
Chemical oxygen demand (COD) ThOD BOD (% of ThOD)	2.52 g O ₂ /g substance 3.13 g O ₂ /g substance 0.69
ThOD BOD (% of ThOD)	0.69
n-Heptane (142-82-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established.
Biochemical oxygen demand (BOD)	1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	0.06 g O ₂ /g substance
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	> 0.5 (5 day(s), Literature study)
Heptane, Branched Cyclic (426260-76-6)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Carbon Dioxide, Liquefied, Under Pressure	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
	Not applicable (morganic)
Methanol (67-56-1)	Deadlink's demandable in the call Deadlink's demandable in contra
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD) Chemical oxygen demand (COD)	0.6 - 1.12 g O ₂ /g substance 1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
	1.5 g O ₂ /g substance
Acetone (67-64-1) Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under
Discharginal auropa demand (DOD)	anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD) ThOD	1.92 g O ₂ /g substance 2.2 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
,	(20 day(s)) 0.012
2.3. Bioaccumulative potential	
HARVEST KING CARB & CHOKE CLEANER	
Bioaccumulative potential	Not established.
Benzene (71-43-2)	
BCF fish 1	< 10 (OECD 305: Bioconcentration: Flow-Through Fish Test, 3 day(s), Leuciscus idus, Flow-through system, Fresh water, Experimental value)
Log Pow	2.13 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
Toluene (108-88-3)	
BCF fish 1	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Log Pow	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
n-Heptane (142-82-5)	
BCF other aquatic organisms 1	552 (BCFBAF v3.00, Calculated value)
Log Pow	4.66 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). Not established.
Heptane, Branched Cyclic (426260-76-6)	
Bioaccumulative potential	Not established.

28/02/2019 EN (English US) 8/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)				
Log Pow	0.83 (Experimental value)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).			
Methanol (67-56-1)	Methanol (67-56-1)			
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)			
Log Pow	-0.77 (Experimental value)			
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).			
Acetone (67-64-1)				
BCF fish 1	0.69 (Pisces)			
BCF other aquatic organisms 1	3			
Log Pow	-0.24 (Test data)			
Bioaccumulative potential	Not bioaccumulative. Not established.			
12.4. Mobility in soil				
Benzene (71-43-2)				
Surface tension	0.029 N/m (20 °C)			
Log Koc	2.13 (log Koc, Calculated value)			
Ecology - soil	Low potential for adsorption in soil.			
Toluene (108-88-3)				
Surface tension	27.73 N/m (25 °C)			
Ecology - soil	Low potential for adsorption in soil.			
n-Heptane (142-82-5)				
Surface tension	19.66 mN/m (25 °C)			
Log Koc	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Low potential for adsorption in soil.			
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)				
Ecology - soil	Not applicable (gas).			
Methanol (67-56-1)				
Surface tension	0.023 N/m (20 °C)			
Log Koc	0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Highly mobile in soil.			
Acetone (67-64-1)				
Surface tension	0.0237 N/m (20 °C)			
12.5. Other adverse effects				
Other information	· Avoid release to the environment			

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1 (Marine Pollutant-Heptane), Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

Flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

28/02/2019 EN (English US) 9/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except **DOT Vessel Stowage Other**

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Subsidiary risks (IMDG) : Marine Pollutant-Heptane

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

HARVEST KING CARB & CHOKE CLEANER 14 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard

Benzene (71-43-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

Toluene (108-88-3)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard Fire hazard

Immediate (acute) health hazard

Heptane, Branched Cyclic (426260-76-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard Delayed (chronic) health hazard

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

SARA Section 311/312 Hazard Classes Sudden release of pressure hazard Immediate (acute) health hazard

Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302 Listed on the United States SARA Section 355

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Delayed (chronic) health hazard Fire hazard

28/02/2019 EN (English US) 10/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA		
HARVEST KING CARB & CHOKE CLEANER 14 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
Benzene (71-43-2)		
Listed on the Canadian DSL (Domestic Substanc	es List)	
Toluene (108-88-3)		
Listed on the Canadian DSL (Domestic Substanc	es List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Heptane, Branched Cyclic (426260-76-6)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Methanol (67-56-1)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Acetone (67-64-1)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Heptane, Branched Cyclic (426260-76-6)

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63 F; R11

T; R39/23/24/25 Xn; R20/21/22 Xn; R48/20 Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

Benzene (71-43-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Toluene (108-88-3)

28/02/2019 EN (English US) 11/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, Branched Cyclic (426260-76-6)

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA under 40 CFR 720.30.

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

13.3. 03 State regulation	3				
HARVEST KING CARB &	CHOKE CLEANER 14 OZ.				
U.S California - Proposition 65 - Carcinogens List		Yes			
U.S California - Proposition 65 - Developmental Toxicity		Yes			
U.S California - Proposition 65 - Reproductive Toxicity - Female		No			
U.S California - Proposition 65 - Reproductive Toxicity - Male		Yes			
State or local regulations		U.S California - Proposition 65			
Benzene (71-43-2)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		
Toluene (108-88-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		
n-Heptane (142-82-5)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Heptane, Branched Cycli	c (426260-76-6)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
	d, Under Pressure (124-38-	9)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Methanol (67-56-1)	•		•		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	Yes	No	No		
	1				

28/02/2019 EN (English US) 12/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		

Benzene (71-43-2)

State or local regulations

U.S. - California - Proposition 65

U.S. - Pennsylvania - RTK (Right to Know) List

New Jersey Right-to-Know

Toluene (108-88-3)

State or local regulations

U.S. - California - Proposition 65

U.S. - New Jersey - Special Health Hazards Substances List

New Jersey Right-to-Know

U.S. - Massachusetts - Right To Know List

Rhode Island Right to Know

U.S. - Michigan - Critical Materials List

U.S. - New Jersey - Environmental Hazardous Substances List

U.S. - Illinois - Toxic Air Contaminants

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65

New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.


Full text of H-phrases:

28/02/2019

H223	Flammable aerosol	
H224	Extremely flammable liquid and vapour	
H225	Highly flammable liquid and vapour	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H304	May be fatal if swallowed and enters airways	
H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H331	Toxic if inhaled	
H336	May cause drowsiness or dizziness	
H361	Suspected of damaging fertility or the unborn child	
H370	Causes damage to organs	
H373	May cause damage to organs through prolonged or repeated	
	exposure	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

EN (English US)



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: 3 - Liquids and solids (including finely divided suspended NFPA fire hazard

solids) that can be ignited under almost all ambient

temperature conditions.

: 0 - Material that in themselves are normally stable, even NFPA reactivity

under fire conditions.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 1 Slight Hazard

Personal protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

28/02/2019 EN (English US) 14/14